


# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>35/65 R 33</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / PALA CARICATRICE / DUMPER<br>DI BASSO PROFILO                                    |
| <b>VERSIONE</b>     | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 229 A2   |



## DIMENSIONI US STANDARD

|                   |          |                    |           |
|-------------------|----------|--------------------|-----------|
| <b>CODICE USA</b> | 94058594 | <b>RIM REC</b>     | 28.00/3.5 |
| <b>OD (IN)</b>    | 81.2     | <b>TRA CODE</b>    | L5        |
| <b>SLR (IN)</b>   | 36.0     | <b>STAR RATING</b> | ★★★       |
| <b>RC (IN)</b>    | 244.7    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 98    | 102   | 105   | 109   | 112   | 116   |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 64000 | 66000 | 68000 | 69500 | 70500 | 71500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.