

AGRIMAX RT 855



AGRIMAX RT 855
RADIAL TRACTOR TIRES

AGRIMAX RT 855



AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.



	SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
				REC RIM	ALT RIM						
		DW	FR								
Ø16"	210/95 R 16 (7.50 R 16)			W 7	W 6 6 LB	214	806	360	2387	370	STD
	180/95 R 16 (6.50 R 16)			5.5 F	6.0 F	185	760	340	2265	350	STD
	210/95 R 16 (7.50 R 16)		116 A8	W 7	W 6 6 LB	214	806	350	2353	370	IMP
Ø18"	210/95 R 18 (7.50 R 18)			W 7	W 6	214	855	385	2565	400	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
250/80 R 18			W 8	W 7 W 9	250	835	375	2539	410	STD
210/95 R 18 (7.50 R 18)		122 A8	W 7	W 6	214	855	378	2565	400	IMP
Ø20"	280/85 R 20 (11.2 R 20)		W 10	W 9	292	984	447	2977	475	STD
	250/85 R 20 (9.5 R 20)		W 8	W 7 W 9	250	940	424	2812	450	STD
	210/95 R 20 (7.50 R 20)		W 7	W 6	214	908	418	2749	425	STD
	280/85 R 20 (11.2 R 20)		W 10	W 9	292	984	441	2952	475	STD
	320/85 R 20 (12.4 R 20)		W 11	W 9 W 10	329	1052	467	3100	500	STD
	210/90 R 20 (8.3 R 20)		W 7	W 6	211	890	412	2681	425	STD
Ø22"	250/85 R 22 (9.5 R 22)		W 8	W 7	251	985	453	2964	475	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
	R1W		176 kg

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
250/85 R 22			W 8	W 7	251	985	453	2964	475	SPL
Ø24"	250/85 R 24 (9.5 R 24)		W 8	W 7 W 9	251	1036	475	3104	500	STD
	340/85 R 24 (13.6 R 24)		W 12	W 11	353	1188	532	3542	575	STD
	420/85 R 24 (16.9 R 24)		W 15 L	W 14 L W 13	450	1324	582	3900	625	SPL
	420/85 R 24 (16.9 R 24)		W 15 L	W 14 L W 13	450	1324	589	3910	625	STD
	280/85 R 24 (11.2 R 24)		W 10	W 9	292	1086	492	3224	525	SPL
	320/85 R 24 (12.4 R 24)		W 11	W 9 W 10	329	1154	519	3424	550	STD
	380/85 R 24 (14.9 R 24)		W 12	W 11 W 13	380	1256	554	3720	600	SPL
	340/85 R 24 (13.6 R 24)		W 12	W 11	353	1188	531	3540	575	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
			
R1W	176 kg		

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
280/85 R 24 (11.2 R 24)			W 10	W 9	292	1086	492	3224	525	STD
380/85 R 24 (14.9 R 24)			W 12	W 11 W 13	380	1256	554	3720	600	STD
320/85 R 24 (12.4 R 24)			W 11	W 9 W 10	329	1154	519	3424	550	SPL
250/85 R 24 (9.5 R 24)			W 8	W 7 W 9	251	1036	475	3104	500	SPL
Ø28"										
			W 8	W 7 W 9	251	1137	519	3421	550	SPL
			W 15 L	W 13 W 14 L	438	1425	638	4241	675	STD
			W 12	W 11	353	1315	603	3963	625	STD
			W 12	W 11 W 13	380	1357	606	4015	650	SPL
			W 11	W 9 W 10	329	1255	569	3743	600	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	 R1W		 176 kg

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
380/85 R 28 (14.9 R 28)			W 12	W 11 W 13	380	1357	606	4015	650	STD
340/85 R 28 (13.6 R 28)			W 12	W 11	353	1289	588	3890	625	STD
420/85 R 28 (16.9 R 28)			W 15 L	W 13 W 14 L	438	1425	638	4241	675	SPL
280/85 R 28 (11.2 R 28)			W 10	W 9	292	1187	545	3558	575	STD
340/85 R 28 (13.6 R 28)			W 12	W 11	353	1289	588	3890	625	SPL
320/85 R 28 (12.4 R 28)			W 11	W 9 W 10	329	1255	569	3743	600	SPL
250/85 R 28 (9.5 R 28)			W 8	W 7 W 9	251	1137	519	3421	550	STD
280/85 R 28 (11.2 R 28)			W 10	W 9	292	1187	545	3558	575	SPL
 460/85 R 30 (18.4 R 30)			W 16 L	W 14 L W 15 L	475	1544	680	4562	725	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
			
			
			

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphics and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	438	1578	709	4702	750	STD
320/85 R 34 (12.4 R 34)			W 11	W 9 W 10	329	1408	645	4280	675	SPL
420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	438	1578	709	4702	750	SPL
460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	475	1646	721	4865	775	SPL
320/85 R 34 (12.4 R 34)			W 11	W 9 W 10	329	1408	645	4280	675	STD
460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	475	1646	721	4865	775	STD
460/85 R 34 (18.4 R 34)			W 16 L	W 14 L W 15 L	475	1646	721	4865	775	STD
420/85 R 34 (16.9 R 34)			W 15 L	W 13 W 14 L	438	1578	728	4782	750	STD
Ø36"										
320/85 R 36 (12.4 R 36)			W 11	W 9 W 10	329	1458	672	4404	700	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
			
R1W	176 kg		

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
340/85 R 36 (13.6 R 36)			W 12	W 11	353	1492	689	4507	725	SPL
340/85 R 36 (13.6 R 36)			W 12	W 11	353	1492	689	4507	725	STD
320/85 R 36			W 11	W 9 W 10	329	1458	672	4404	700	STD
320/85 R 36 (12.4 R 36)			W 11	W 9 W 10	329	1458	672	4404	700	STD
Ø38"			W 11	W 9 W 10 DW 10 DW 11	329	1509	700	4580	725	STD
			DW 16 L	DW 18 L DD 16 L	516	1849	813	5466	875	STD
			DW 16 L	DW 18 L DD 16 L	516	1849	847	5595	875	STD
			W 12	W 11 W 13	380	1611	736	4842	775	SPL
			W 15 L	W 13 W 14 L	438	1679	763	5014	800	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
340/85 R 38 (13.6 R 38)			W 12	W 11	353	1543	712	4668	750	SPL
480/80 R 38 (18.4 R 38)			DW 16 L	W 14 L W 15 L	475	1747	785	5161	825	STD
460/85 R 38 (18.4 R 38)			W 16 L	W 14 L W 15 L	475	1747	785	5205	825	SPL
380/85 R 38 (14.9 R 38)			W 12	W 11 W 13	380	1611	736	4842	775	STD
420/85 R 38 (16.9 R 38)			W 15 L	W 13 W 14 L	438	1679	763	5014	800	SPL
520/85 R 38			DW 16 L	DW 18 L DD 16 L	516	1849	847	5595	875	SPL
460/85 R 38 (18.4 R 38)			W 16 L	W 14 L W 15 L	475	1747	785	5205	825	STD
520/85 R 38 (20.8 R 38)			DW 16 L	DW 18 L DD 16 L	516	1849	813	5466	875	SPL
320/85 R 38 (12.4 R 38)			W 11	W 9 W 10 DW 10	329	1509	700	4580	725	SPL

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
			
			

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
340/85 R 38 (13.6 R 38)			W 12	W 11	353	1543	712	4668	750	STD
Ø42"	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	540	1951	895	5919	925	SPL
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	516	1951	858	5782	925	SPL
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	516	1951	858	5782	925	STD
	520/85 R 42 (20.8 R 42)		DW 16 L W 16 A DD 16	DW 18 A DD 18 W 18 A DD 18 L	540	1951	895	5919	925	STD
	480/80 R 42 (18.4 R 42)		W 16 A DD 16 DW 16 A	DD 16 L DW 16 L W 16 L	479	1835	835	5495	875	STD
Ø46"	420/80 R 46 (16.9 R 46)		W 13	W 12	418	1840	863	5641	900	STD
	520/85 R 46 (20.8 R 46)		DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	516	2052	930	6157	975	STD
	480/80 R 46 (18.4 R 46)		DW 16 A W 16 A DD 16	W 16 L DD 16 L DW 16 L	479	1936	895	5871	925	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
	 R1W		 176 kg

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026

SIZE	LI/SS		RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
	DW	FR								
420/80 R 46 (16.9 R 46)			W 13	W 12	418	1840	863	5641	900	STD
480/80 R 46 (18.4 R 46)			DW 16 A W 16 A DD 16	W 16 L DD 16 L DW 16 L	479	1936	895	5871	925	STD
520/85 R 46 (20.8 R 46)			DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	516	2075	964	6310	975	STD
420/80 R 46 (16.9 R 46)			W 13	W 12	418	1840	863	5641	900	SPL
520/85 R 46			DW 16 L W 16 A W 16 L DD 16	DW 18 L W 18 L W 18 A	516	2052	930	6157	975	SPL
Ø50"										
			DW 16 L	DW 15 L W 15 L	489	2036	941	6183	975	STD
			DW 16L	DW 18 L	516	2154	992	6472	1025	STD
			W 13	W 12	418	1951	915	5955	950	SB
480/80 R 50 (18.4 R 50)			DW 16 L	DW 15 L W 15 L	489	2036	945	6183	975	SB

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED, IMP: IMPLEMENT

TECHNOLOGIES		PERFORMANCES	
			
	R1W		176 kg

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026



TECHNOLOGIES		PERFORMANCES	
	 R1W		
	 176 kg		

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 23/09/2026