

# EARTHMAX SR 55

|                     |                                 |
|---------------------|---------------------------------|
| <b>TIRE SIZE</b>    | 20.5 R 25                       |
| <b>UM</b>           | US STANDARD                     |
| <b>CONSTRUCTION</b> |                                 |
| <b>MACHINERY</b>    | DOZER / LOAD HAUL DUMP / LOADER |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND          |
| <b>TIRE TYPE</b>    | TL                              |
| <b>LI/SS</b>        | 193 A2                          |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94062348 | <b>RIM REC</b>     | 17.00/2.0 |
| <b>OD (IN)</b>  | 60.7     | <b>TRA CODE</b>    | L5S       |
| <b>SLR (IN)</b> | 27.6     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 182.8    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 21500 | 22000 | 22700 | 24000 | 24700 | 25400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.