


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>IF 680/85 R 32</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / SPARGITORE / TRATTORE / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	179 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	682	<b>RIM REC</b>	DW23 B
<b>OD (MM)</b>	1960	<b>RIM ALT</b>	DW21 B
<b>SLR (MM)</b>	846	<b>ECE</b>	E11-106R-006401
<b>RC (MM)</b>	5860	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>FROM 65 TO 40</b>	3640	4185	4805	5425	6045	6665	7285	7750
<b>30</b>	3785	4350	4995	5640	6285	6930	7575	8060
<b>20</b>	3930	4515	5185	5855	6525	7195	7865	8370
<b>10</b>	4620	5310	6100	6885	7675	8460	9250	9840
<b>UPTO 30 CYC</b>	4730	5440	6245	7050	7855	8660	9470	10075
<b>UPTO 15 CYC</b>	5640	6485	7445	8405	9365	10330	11290	12010
<b>10 HT</b>	3785	4350	4995	5640	6285	6930	7575	8060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.