

# AGRIMAX RT 855

|           |                                                                                 |
|-----------|---------------------------------------------------------------------------------|
| TIRE SIZE | 320/85 R 38                                                                     |
| UM        | US STANDARD                                                                     |
| MACHINERY | PULVERIZADOR / VENDIMIADORA /<br>TRACTOR / COSECHADORA /<br>MAQUINARIA AGRÍCOLA |
| VERSIÓN   | SPECIAL                                                                         |
| TIRE TYPE | TL                                                                              |
| LI/SS     | 143 A8/B                                                                        |



## DIMENSIONES US STANDARD

|            |          |                                 |                    |
|------------|----------|---------------------------------|--------------------|
| CÓDIGO USA | 94047543 | RIM ALT                         | W 9 ; W 10 ; DW 10 |
| SW (IN)    | 13.0     | ECE                             | E4-106R-000781     |
| OD (IN)    | 59.4     | TRA CODE                        | R1W                |
| SLR (IN)   | 27.6     | TREAD DEPTH (32 <sup>nd</sup> ) | 52.29              |
| RC (IN)    | 180.3    | TMPH (TM/H)                     | 0                  |
| RIM REC    | W 11     |                                 |                    |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   |
|-----------|------|------|------|------|------|------|------|------|------|
| 30        | 2170 | 2520 | 3310 | 4030 | 4390 | 4700 | 5110 | 5530 | 6000 |
| 25        | 2170 | 2520 | 3310 | 4030 | 4390 | 4700 | 5110 | 5530 | 6000 |
| 20        | 2330 | 2710 | 3550 | 4320 | 4710 | 5030 | 5480 | 5930 | 6440 |
| 5 LT      | 2910 | 3390 | 4440 | 5400 | 5890 | 6290 | 6860 | 7420 | 8060 |
| 5 HT      | 2330 | 2710 | 3550 | 4320 | 4710 | 5030 | 5480 | 5930 | 6440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.