


# AGRIMAXFACTOR

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>420/70 R 24</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 130 D ; 133 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 418  | <b>RIM REC</b> | W 13            |
| <b>OD (MM)</b>  | 1248 | <b>RIM ALT</b> | W 12; W 14 L    |
| <b>SLR (MM)</b> | 550  | <b>ECE</b>     | E11-106R-007640 |
| <b>RC (MM)</b>  | 3649 | <b>SRI</b>     | 600             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1045 | 1220 | 1390 | 1560 | 1730 | 1900 |
| 50         | 1100 | 1280 | 1460 | 1640 | 1820 | 1995 |
| 40         | 1150 | 1335 | 1525 | 1710 | 1900 | 2085 |
| 30         | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |
| 10 LT      | 1405 | 1635 | 1865 | 2095 | 2325 | 2550 |
| 10 HT      | 1205 | 1400 | 1600 | 1795 | 1990 | 2185 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.