DATA SHEET

PRINTED ON
23-04-2026

RIB MASTER

TIRE SIZE	**215/75 - 17.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	PRESĂ DE BALOTAT / MAȘINI DE IMPLEMENTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS FREE ROLLING	142 A8

DIMENSIUNI US STANDARD

USA CODE	94010905	**RC (IN)**	90.9
SW (IN)	8.7	**RIM REC**	6.75
OD (IN)	30.5	**ECE**	E11-106R-004593
SLR (IN)	14.2	**PR**	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	131
5 FR	8130
15 FR	6960
20 FR	6550
25 FR	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..