

# RIB 774 (A)

<b>TIRE SIZE</b>	250/65 - 14.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	124 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94027255	<b>RC (IN)</b>	77.9
<b>SW (IN)</b>	10.0	<b>RIM REC</b>	AG 8.00
<b>OD (IN)</b>	27.2	<b>RIM ALT</b>	6.75
<b>SLR (IN)</b>	11.9	<b>ECE</b>	E11-106R-003374

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>80</b>
5 FR	4940
15 FR	4200
20 FR	3950
25 FR	3530

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.