

# TR 317

<b>TIRE SIZE</b>	<b>18X8.50 - 8</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	215	<b>RIM REC</b>	7.00 I - 55; I - 70; I - 90
<b>OD (MM)</b>	450	<b>ECE</b>	E11-106R-003495
<b>SLR (MM)</b>	198	<b>PR</b>	4
<b>RC (MM)</b>	1305		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>1.50</b>
15	375

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.