


AGRIMAX FORCE

TIRE SIZE	IF 900/50 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	180 D



РАЗМЕРЫ IS STANDARD

SW (MM)	881	RIM REC	DW 30 B
OD (MM)	1955	RIM ALT	TW 30 B
SLR (MM)	872	ECE	E11-106R-006492
RC (MM)	5830	SRI	950

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	3345	3855	4440	4950	5530	6040	6770	7280
FROM 65 TO 40	3680	4240	4880	5440	6080	6640	7440	8000
30	3825	4405	5075	5655	6320	6905	7735	8320
20	3970	4575	5270	5875	6565	7170	8035	8640
10	4670	5380	6195	6905	7720	8430	9445	10160
UPTO 30 CYC	4780	5510	6340	7070	7900	8630	9670	10400
UPTO 15 CYC	5700	6570	7560	8430	9420	10290	11530	12400
UPTO 10 CYC	6255	7205	8295	9245	10335	11285	12645	13600
10HT	3825	4405	5075	5655	6320	6905	7735	8320

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.