


AGRIMAX FORCE



| | |
|---------------------|--|
| TIRE SIZE | IF 600/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 164 D |

DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 603 | RIM REC | DW 21 B |
| OD (MM) | 1551 | RIM ALT | DW 20 B |
| SLR (MM) | 694 | ECE | E4-106R-000795 |
| RC (MM) | 4654 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|---------------------------------------|------|------|------|------|------|------|------|------|
| 70 | 2135 | 2455 | 2820 | 3185 | 3545 | 3910 | 4275 | 4550 |
| FROM 65 TO 40 | 2350 | 2700 | 3100 | 3500 | 3900 | 4300 | 4700 | 5000 |
| 30 | 2440 | 2805 | 3220 | 3640 | 4055 | 4470 | 4885 | 5200 |
| 20 | 2535 | 2915 | 3345 | 3780 | 4210 | 4640 | 5075 | 5400 |
| 10 | 2980 | 3425 | 3935 | 4445 | 4950 | 5460 | 5965 | 6350 |
| *UPTO 10 CYC WITH FRONT LOADER | 3290 | 3780 | 4340 | 4900 | 5460 | 6020 | 6580 | 7000 |
| 10 HT | 2440 | 2805 | 3220 | 3640 | 4055 | 4470 | 4885 | 5200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.