


# EARTHMAX SR 22 AS

<b>TIRE SIZE</b>	23.5 R 25
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PALA CARICATRICE / MOTOLIVELLATRICE
<b>VERSIONE</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	185 B ; 170 A8 ; 201 A2



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94073405	<b>RIM REC</b>	19.50/2.5
<b>OD (IN)</b>	63.5	<b>TRA CODE</b>	E2/G2/L2
<b>SLR (IN)</b>	27.9	<b>STAR RATING</b>	★★/★/★★
<b>RC (IN)</b>	191.5		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	16500	17100	18200	18700	19800	20400	-	-	-	-
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	27600	28300	29100	30000	30900
MPH / PSI	94																	
30	-																	
25	-																	
5	32000																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.