DATA SHEET

Ultimo aggiornam
2-06-2026

RT 747 AGRO INDUSTRIAL

TIRE SIZE	**460/70 R 24**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	PALA COMPATTA / SOLLEVATORE TELESCOPICO / PALA COMPATTA / SOLLEVATORE TELESCOPICO
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	152 A8/B

DIMENSIONI US STANDARD

CODICE USA	94016815	**RC (IN)**	151.2
SW (IN)	18.3	**RIM REC**	DW 15 L
OD (IN)	49.4	**RIM ALT**	DW 14 L ; DW 16 L
SLR (IN)	21.9	**ECE**	E11-106R-004071

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46
30	3680	4540	5320	6180	6970	7830
25	3680	4540	5320	6180	6970	7830
20	3940	4860	5700	6610	7450	8380
15	4080	5040	5910	6870	7730	8690
5 CYC	5520	6810	7980	9270	10450	11740
STATIC	7730	9530	11180	12980	14630	16430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..