


# AGRIMAX V-FLECTO



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>VF 480/80 R 38</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MOTORSTARK TRAKTOR / TRAKTOR   |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 166 D  |

## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 479  | <b>RIM REC</b> | DW 16 L         |
| <b>OD (MM)</b>  | 1733 | <b>RIM ALT</b> | DW 15 L         |
| <b>SLR (MM)</b> | 774  | <b>ECE</b>     | E11-106R-007168 |
| <b>RC (MM)</b>  | 5169 | <b>SRI</b>     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR                            | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|---------------------------------------|------|------|------|------|------|------|------|------|
| 70                                    | 2270 | 2605 | 2990 | 3375 | 3760 | 4150 | 4535 | 4820 |
| <b>FROM 65 TO 40</b>                  | 2495 | 2865 | 3290 | 3710 | 4135 | 4560 | 4985 | 5300 |
| 30                                    | 2545 | 2920 | 3355 | 3785 | 4220 | 4650 | 5085 | 5405 |
| 20                                    | 2590 | 2980 | 3420 | 3860 | 4300 | 4740 | 5180 | 5510 |
| 10                                    | 2745 | 3150 | 3615 | 4085 | 4550 | 5015 | 5485 | 5830 |
| <b>*UPTO 10 CYC WITH FRONT LOADER</b> | 3490 | 4010 | 4605 | 5195 | 5790 | 6385 | 6975 | 7420 |
| 10 HT                                 | 2545 | 2830 | 3355 | 3785 | 4220 | 4650 | 5085 | 5405 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.