


AGRIMAX V- FLECTO

| | |
|--------------|--|
| TIRE SIZE | VF 580/85 R 46 CFO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | FELDSPRITZE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 179 D |



ABMESSUNGEN IS STANDARD

| | | | |
|----------|------|---------|------------------|
| SW (MM) | 605 | RIM REC | DW 20 B |
| OD (MM) | 2156 | RIM ALT | DW 21 B, DW18L |
| SLR (MM) | 947 | ECE | E11-106R-0011691 |
| RC (MM) | 6451 | SRI | 1025 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1 | 1.2 | 1.4 | 1.6 | 2 |
|---------------|------|------|------|------|------|-------|-------|
| 70 | 3530 | 4095 | 4660 | 5295 | 5860 | 6425 | 7055 |
| FROM 65 TO 40 | 3875 | 4495 | 5115 | 5815 | 6435 | 7055 | 7750 |
| 30 | 3955 | 4585 | 5220 | 5930 | 6565 | 7195 | 7905 |
| 20 | 4030 | 4675 | 5320 | 6045 | 6690 | 7335 | 8060 |
| 10 | 4265 | 4945 | 5630 | 6395 | 7080 | 7760 | 8525 |
| 10HT | 3955 | 4585 | 5220 | 5930 | 6565 | 7195 | 7905 |
| UPTO 10 CYC | 5755 | 6680 | 7600 | 8635 | 9555 | 10475 | 11510 |
| UPTO 15 CYC | 5255 | 6095 | 6935 | 7880 | 8720 | 9560 | 10505 |
| UPTO 30 CYC | 4400 | 5105 | 5810 | 6600 | 7305 | 8010 | 8800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.