

FLOTATION 648

| | |
|---------------------------|----------------------------|
| TYRE SIZE | 600/50 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | HAY HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 147 A8/144 B |
| LI/SS FREE ROLLING | 159 A8/156 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94006397 | RC (IN) | 137.8 |
| SW (IN) | 24.1 | RIM REC | AG 20.00 |
| OD (IN) | 46.1 | ECE | E4-106R-002312 |
| SLR (IN) | 20.1 | PR | 12 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 22 | 25 | 29 |
|--------------|-------|-------|-------|
| 5 FR | 11410 | 12280 | 13500 |
| 10 FR | 10260 | 11060 | 12160 |
| 20 FR | 9130 | 9830 | 10800 |
| 25 FR | 8150 | 8770 | 9640 |
| 30 FR | 7330 | 7890 | 8820 |
| 5 DW | 8020 | 8630 | 9490 |
| 10 DW | 7220 | 7760 | 8540 |
| 20 DW | 6420 | 6900 | 7590 |
| 25 DW | 5730 | 6160 | 6780 |
| 30 DW | 5160 | 5540 | 6170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.