


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>600/65 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	155 D ; 158 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1542	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	697	<b>ECE</b>	E4-106R-001825
<b>RC (MM)</b>	4609	<b>SRI</b>	725

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	1860	2170	2445	2715	2985	3220	3565	3875
<b>50</b>	1955	2280	2565	2850	3135	3380	3745	4070
<b>40</b>	2040	2380	2680	2975	3275	3530	3910	4250
<b>30</b>	2145	2500	2810	3125	3435	3705	4105	4460
<b>10 LT</b>	2495	2910	3275	3640	4005	4315	4780	5195
<b>10 HT</b>	2145	2500	2810	3125	3435	3705	4105	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.