


AGRIMAX FORCE

TIRE SIZE	IF 710/75 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	178 D



DIMENSÕES US STANDARD

CÓDIGO USA	94053643	RC (IN)	227.4
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	75.9	RIM ALT	DW 23 B
SLR (IN)	34.3	ECE	E11-106R-003017

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7070	8120	9330	10530	11730	12930	14140	15050
FROM 40 TO 25	7770	8930	10250	11570	12900	14220	15540	16500
20	8080	9280	10660	12040	13400	14780	16160	17200
12	8390	9630	11070	12500	13920	15350	16780	17860
5	9870	11330	13020	14690	16370	18050	19730	21000
UPTO 20 CYC	10100	11610	13330	15050	16770	18480	20200	21490
UPTO 10 CYC	12040	13830	15880	17930	19980	22030	24080	25630
UPTO 5 CYC	13200	15180	17430	19680	21920	24170	26420	28110
5 HT	8080	9280	10660	12040	13400	14780	16160	17200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.