


# AS 504

<b>TIRE SIZE</b>	7.50 - 16
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	TELESKOPLASTARE / ÅKERSLÄP / ARBETSFORDON / TELESKOPLASTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	99 A8
<b>LI/SS FREE ROLLING</b>	112 A8



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	209	<b>RIM REC</b>	5.50 F
<b>OD (MM)</b>	803	<b>RIM ALT</b>	4.50 E; 5.00 F; 4.00 E; 5 K; 6 LB; 6.00 F
<b>SLR (MM)</b>	372	<b>ECE</b>	E4-106R-002633
<b>RC (MM)</b>	2475	<b>PR</b>	8

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.20</b>
10 FR	1570
25 FR	1335
30 FR	1255
40 FR	1120
10 DW	1085
25 DW	920
30 DW	870
40 DW	775

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.