DATA SHEET

PRINTED ON
21-04-2026

EARTHMAX SR 55

TIRE SIZE	**35/65 R 33**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	DOZER / PALA LHD / PALA CARICATRICE
VERSIONE	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	224 A2

DIMENSIONI IS STANDARD

OD (MM)	2065	**TRA CODE**	L5S
SLR (MM)	915	**STAR RATING**	★★
RC (MM)	6175		
RIM REC	28.00/3.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	5.25	5.50	5.75	6.00	6.25	6.50
10	23600	25000	25750	26500	27250	28000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..