


AGRIMAX RT 855

TIRE SIZE	250/80 R 18
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	125 A8 ; 125 B



DIMENSIUNI US STANDARD

USA CODE	94066131	RC (IN)	100.0
SW (IN)	9.8	RIM REC	W 8
OD (IN)	32.9	RIM ALT	W 7; W 9
SLR (IN)	14.8	ECE	E11-106R-006605

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	57	52	58
30	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	3460	3640
25	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	2460	3640
20	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900
5 LT	1720	2010	2300	2590	2890	3130	3470	3670	4010	4350	4640	4880
5 HT	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.