


# AW 09

<b>TIRE SIZE</b>	<b>320/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	MAQUINARIA AGRÍCOLA / REMOLQUE / EMPACADORA DE HENO / COSECHADORA / COSECHADORA / MAQUINARIA AGRÍCOLA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	133 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	309	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	901	<b>ECE</b>	E4-106R-000378
<b>SLR (MM)</b>	392		
<b>RC (MM)</b>	2640		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2885
25 DW	2450
30 DW	2305
40 DW	2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.