

# FLOTATION 558

<b>TIRE SIZE</b>	<b>500/45 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / TANKBIL / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	136 A8/132 B
<b>LI/SS FREE ROLLING</b>	148 A8/144 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1045	<b>ECE</b>	E4-106R-002307
<b>SLR (MM)</b>	471	<b>PR</b>	12
<b>RC (MM)</b>	3167		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.30	2.50	2.70
10 FR	4020	4215	4410
20 FR	3615	3795	3970
30 FR	3215	3370	3530
40 FR	2870	3010	3150
50 FR	2585	2710	2800
10 DW	2855	2995	3135
20 DW	2570	2695	2820
30 DW	2285	2395	2510
40 DW	2040	2140	2240
50 DW	1835	1925	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.