


# AGRIMAXFACTOR

<b>TIRE SIZE</b>	<b>520/70 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	150 D ; 153 A8



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94070725	<b>RC (IN)</b>	206.3
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	68.9	<b>RIM ALT</b>	W 15 L ; W 18 L
<b>SLR (IN)</b>	31.3	<b>ECE</b>	E11-106R-007609

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	4070	4730	5400	6060	6720	7390
30	4280	4970	5670	6370	7070	7760
25	4450	5180	5910	6640	7360	8090
20	4680	5450	6210	6980	7740	8500
5 LT	5450	6340	7230	8120	9020	9900
5 HT	4680	5450	6210	6980	7740	8500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.