


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>280/85 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	122 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	292	<b>RIM REC</b>	W 10
<b>OD (MM)</b>	984	<b>RIM ALT</b>	W 9
<b>SLR (MM)</b>	447	<b>ECE</b>	E11-106R-007936
<b>RC (MM)</b>	2977	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>50</b>	615	720	825	930	1035	1125	1335	1500
<b>40</b>	615	720	825	930	1035	1125	1335	1500
<b>30</b>	660	775	885	1000	1110	1205	1430	1605
<b>10 LT</b>	825	965	1110	1250	1390	1510	1790	2010
<b>10 HT</b>	660	775	885	1000	1110	1205	1430	1605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.