

# RIB 774 (A)

|                           |              |
|---------------------------|--------------|
| <b>TIRE SIZE</b>          | 10.5/65 - 16 |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS         |
| <b>VERSION</b>            | INDUSTRIAL   |
| <b>TIRE TYPE</b>          | TT           |
| <b>LI/SS FREE ROLLING</b> | 130 A8       |



## DIMENSIONS IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 265  | <b>RIM REC</b> | W 9             |
| <b>OD (MM)</b>  | 745  | <b>RIM ALT</b> | W 8 L           |
| <b>SLR (MM)</b> | 339  | <b>ECE</b>     | E11-106R-004313 |
| <b>RC (MM)</b>  | 2183 | <b>PR</b>      | 14              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>5.30</b> |
|-------------------|-------------|
| 10 FR             | 2660        |
| 25 FR             | 2260        |
| 30 FR             | 2130        |
| 40 FR             | 1900        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.