

# FLOTATION 648

<b>TIRE SIZE</b>	<b>750/60 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	164 A8/160 B
<b>LI/SS FREE ROLLING</b>	176 A8/172 B



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94006533	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	29.7	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	65.9	<b>ECE</b>	E11-106R-003410
<b>SLR (IN)</b>	28.0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
<b>5 FR</b>	20370	21150	21910
<b>10 FR</b>	18330	19040	19720
<b>20 FR</b>	16290	16930	17530
<b>25 FR</b>	14550	15110	15650
<b>30 FR</b>	13090	13600	13890
<b>5 DW</b>	14340	14890	15430
<b>10 DW</b>	12910	13400	13890
<b>20 DW</b>	11460	11920	12350
<b>25 DW</b>	10240	10640	11020
<b>30 DW</b>	9210	9580	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.