

AGRIMAX RT 765

TIRE SIZE	520/70 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	148 D



РАЗМЕРЫ US STANDARD

USA CODE	94063192	RC (IN)	194.0
SW (IN)	20.3	RIM REC	W 16 L
OD (IN)	64.6	RIM ALT	W 15 L; W 18 L
SLR (IN)	29.1	ECE	E11-106R-005831

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	90	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.