


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 620/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	620	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1935	<b>RIM ALT</b>	DW 20 B; DW 23 B
<b>SLR (MM)</b>	849	<b>ECE</b>	E11-106R-0011233
<b>RC (MM)</b>	5795	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3140	3640	4145	4710	5210	5715	6275
FROM 65 TO 40	3450	4005	4555	5175	5730	6280	6900
30	3520	4085	4645	5280	5840	6405	7035
20	3590	4165	4740	5385	5960	6530	7175
10	3795	4405	5010	5695	6300	6910	7590
*UPTO 10 CYC WITH FRONT LOADER	4830	5605	6380	7245	8020	8795	9660
10HT	3520	4085	4645	5280	5840	6405	7035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.