


# CON STAR

<b>TIRE SIZE</b>	<b>440/80 - 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / КОМПАКТНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	INDUSTRIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	156 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94051199	<b>RC (IN)</b>	169.3
<b>SW (IN)</b>	17.7	<b>RIM REC</b>	DW 14 L
<b>OD (IN)</b>	55.9	<b>RIM ALT</b>	DW 13; DW 13 L; DW 15 L
<b>SLR (IN)</b>	24.9	<b>ECE</b>	E11-106R-003035

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>46</b>
25	8820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.