

MULTIMAX MP 522

340/80 R 20 IND

UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ / KÜÇÜK YÜKLEYİCİ / TELESKOPIK YÜKLEYİCİ
VERSION	STANDARD
TIRE TYPE	TL
	144 A8/B



UNDEFINED US STANDARD

USA CODE	94052875	RC (IN)	126.5
SW (IN)	13.5	RIM REC	11
OD (IN)	41.4	RIM ALT	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC
SLR (IN)	18.9	ECE	E11-106R-002969

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2970	3530	4010	4570	5130	5500	6170	-	-
25	2970	3530	4010	4570	5130	5500	6170	-	-
20	3170	3770	4300	4890	5490	5890	6610	-	-
15	3300	3910	4460	5080	5700	6110	6860	-	-
5 CYC.	3620	4450	5240	6020	6860	7460	8430	8900	9260
STATIC	5540	6820	8020	9240	10520	11430	12930	13630	14200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.