

AGRIMAX V-FLECTO

TIRE SIZE	VF 520/70 R 38
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	SPECIAL
TIRE TYPE	TL
LI/SS	164 D



DIMENSÕES IS STANDARD

SW (MM)	536	RIM REC	DW 18 L
OD (MM)	1750	ECE	E11-106R-0011692
SLR (MM)	773	SRI	825
RC (MM)	5213	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6	2
70	2275	2640	3005	3415	3780	4145	4550
FROM 65 TO 40	2500	2900	3300	3750	4150	4550	5000
30	2550	2960	3370	3825	4235	4645	5100
20	2600	3020	3435	3900	4320	4735	5200
10	2750	3190	3630	4125	4565	5005	5500
10HT	2550	2958	3366	3825	4233	4641	5100
UPTO 10 CYC	3715	4310	4905	5570	6165	6760	7425
UPTO 15 CYC	3390	3930	4475	5085	5625	6170	6775
UPTO 30 CYC	2840	3295	3750	4260	4715	5165	5675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.