


AGRIMAX V- FLECTO

TIRE SIZE	VF 620/70 R 42
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	175 D



DIMENSIONS IS STANDARD

SW (MM)	620	RIM REC	DW 21 B
OD (MM)	1935	RIM ALT	DW 20 B; DW 23 B
SLR (MM)	849	ECE	E11-106R-0010829
RC (MM)	5795	SRI	925

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	3140	3640	4145	4710	5210	5715	6275
FROM 65 TO 40	3450	4005	4555	5175	5730	6280	6900
30	3520	4085	4645	5280	5840	6405	7035
20	3590	4165	4740	5385	5960	6530	7175
10	3795	4405	5010	5695	6300	6910	7590
UPTO 30 CYC	3915	4545	5170	5875	6500	7130	7830
UPTO 15 CYC	4675	5425	6170	7010	7760	8505	9345
UPTO 10 CYC	5125	5945	6765	7685	8505	9325	10245
10HT	3520	4085	4645	5280	5840	6405	7035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.