

AW 705

| | |
|---------------------------|---|
| REIFENGRÖSSE | 400/55 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 154 A8 |



ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 405 | RIM REC | AG 11.75 |
| OD (MM) | 1016 | RIM ALT | 12.25; AG 13.00 |
| SLR (MM) | 443 | ECE | E11-106R-004550 |
| RC (MM) | 3072 | PR | 18 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 4.50 |
|------------|------|
| 10 FR | 5250 |
| 25 FR | 4465 |
| 30 FR | 4200 |
| 40 FR | 3750 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.