

AS 504

TIRE SIZE	6.5/80 - 12
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	72 A8
LI/SS FREE ROLLING	84 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	169	RIM REC	5 J
OD (MM)	608	RIM ALT	5 JA
SLR (MM)	283	ECE	E11-106R-003440
RC (MM)	1836	PR	4

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	2.40
10 FR	700
25 FR	595
30 FR	560
40 FR	500
10 DW	495
25 DW	420
30 DW	400
40 DW	355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.