

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>360/70 R 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	122 D



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94063130	<b>RC (IN)</b>	133.7
<b>SW (IN)</b>	14.1	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	45.4	<b>RIM ALT</b>	W 10; W 12
<b>SLR (IN)</b>	20.4	<b>ECE</b>	E11-106R-005824

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	1820	2120	2410	2710	3010	3310
30	1920	2230	2540	2850	3160	3470
25	2000	2330	2660	2980	3310	3630
20	2090	2440	2780	3120	3460	3800
5 LT	2450	2840	3240	3640	4030	4430
5 HT	2090	2440	2780	3120	3640	3800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.