

AGRIMAX FORCE

TIRE SIZE	IF 710/55 R 28 CFO
UM	IS STANDARD
MACHINERY	COSECHADORA / TRACTOR DE ALTA POTENCIA / TRACTOR
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	165 D



DIMENSIONES IS STANDARD

SW (MM)	716	ECE	E11-106R-005498
OD (MM)	1493	SRI	700
SLR (MM)	663	TRA CODE	R1W
RC (MM)	4442	TREAD DEPTH (MM)	55,5
RIM REC	DW 25 B	TKPH (TK/H)	0

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2150	2475	2855	3185	3555	3885	4350	4685
FROM 65 TO 40	2365	2725	3140	3500	3910	4270	4785	5150
30	2455	2830	3265	3640	4065	4440	4975	5355
20	2550	3940	3390	3780	4220	4610	5165	5560
10	3000	3460	3985	4445	4965	5420	6075	6540
UPTO 30 CYC	3070	3540	4080	4550	5080	5550	6220	6695
UPTO 15 CYC	3665	4220	4865	5425	6060	6615	7415	7980
UPTO 10 CYC	4020	4630	5335	5950	6645	7255	8130	8755
10 HT	2455	2830	3265	3640	4065	4440	4975	5355

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.