

AGRIMAX RT 600

620/75 R 26**UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** BIÇERDÖVER / YAYICI / TRAKTÖR /
UYGULAMALI MAKINE**VERSION** STANDARD**TIRE TYPE** TL

167 A8/B



UNDEFINED IS STANDARD

SW (MM)	625	RIM REC	DW 20 B
OD (MM)	1590	ECE	E11-106R-002993
SLR (MM)	730	SRI	750
RC (MM)	4851		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2510	2890	3545	3870	4255	4635	5015	5450	-	-
40	2510	2890	3545	3870	4255	4635	5015	5450	-	-
30	2685	3095	3795	4145	4555	4960	5370	5835	-	-
10 LT	3365	3875	4750	5190	5700	6210	6725	7305	-	-
10 HT	2685	3095	3795	4145	4555	4960	5370	5835	-	-
10 CYC.	-	4125	5285	5795	6720	7370	8065	8760	8895	9265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.