


# RIDEMAX FROST

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>440/80 R 28 IND</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ТРАКТОР-ТЯГАЧ  |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 156 A8 ; 151 D   |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                  |
|-----------------|----------|----------------|------------------|
| <b>USA CODE</b> | 94513338 | <b>RC (IN)</b> | 169.1            |
| <b>SW (IN)</b>  | 17.4     | <b>RIM REC</b> | DW 14 L          |
| <b>OD (IN)</b>  | 55.9     | <b>RIM ALT</b> | DW 15 L          |
| <b>SLR (IN)</b> | 25.3     | <b>ECE</b>     | E11-106R-0010949 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35    | 38    | 41    | 44    | 46    |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 45        | 3350 | 4420 | 5320 | 5860 | 6240  | 6550  | 6840  | 7230  | 7610  |
| 30        | 3630 | 4770 | 5760 | 6340 | 6750  | 7080  | 7410  | 7810  | 8220  |
| 25        | 3880 | 5110 | 6170 | 6790 | 7230  | 7580  | 7940  | 8380  | 8820  |
| 20        | 4020 | 5300 | 6390 | 7030 | 7480  | 7860  | 8220  | 8670  | 9130  |
| 10        | 4220 | 5570 | 6710 | 7390 | 7870  | 8260  | 8630  | 9120  | 9590  |
| 5         | 4830 | 6360 | 7670 | 8440 | 8990  | 9420  | 9870  | 10420 | 10960 |
| 3         | 5600 | 7370 | 8910 | 9790 | 10430 | 10930 | 11440 | 12080 | 12710 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.