

# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/70 R 24</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL                   |
| <b>MACHINERY</b>    | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 116 D  |



## РАЗМЕРЫ IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 319  | <b>RIM REC</b> | W 10            |
| <b>OD (MM)</b>  | 1094 | <b>RIM ALT</b> | W 9; W 11       |
| <b>SLR (MM)</b> | 502  | <b>ECE</b>     | E11-106R-005827 |
| <b>RC (MM)</b>  | 3245 | <b>SRI</b>     | 525             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|-----|------|------|------|------|------|
| 65         | 690 | 800  | 915  | 1025 | 1140 | 1250 |
| 50         | 725 | 845  | 960  | 1080 | 1200 | 1315 |
| 40         | 755 | 880  | 1005 | 1125 | 1250 | 1370 |
| 30         | 795 | 925  | 1055 | 1185 | 1315 | 1440 |
| 10 LT      | 925 | 1075 | 1225 | 1375 | 1525 | 1675 |
| 10 HT      | 795 | 925  | 1055 | 1185 | 1315 | 1440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.