


AGRIMAX RT 765

| | |
|---------------------|---|
| TIRE SIZE | 420/70 R 24 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 134 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 418 | RIM REC | W 13 |
| OD (MM) | 1248 | RIM ALT | W 12; W 14 L |
| SLR (MM) | 554 | ECE | E11-106R-005825 |
| RC (MM) | 3680 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|------------|------|------|------|------|------|------|------|
| 65 | 1060 | 1230 | 1400 | 1590 | 1760 | 1930 | 2120 |
| 50 | 1115 | 1295 | 1475 | 1675 | 1855 | 2030 | 2230 |
| 40 | 1165 | 1350 | 1535 | 1745 | 1930 | 2120 | 2325 |
| 30 | 1220 | 1420 | 1615 | 1830 | 2030 | 2225 | 2440 |
| 10 LT | 1425 | 1655 | 1880 | 2135 | 2365 | 2590 | 2845 |
| 10 HT | 1220 | 1420 | 1615 | 1830 | 2030 | 2225 | 2440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.