

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 650/65 R 38 CFO                                                                       |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR                                              |
| VERSION      | STANDARD                                                                                 |
| TL/TT        | TL                                                                                       |
| LI/SS        | 169 D                                                                                    |



## DIMENSIONS IS STANDARD

|          |      |          |                 |
|----------|------|----------|-----------------|
| SW (MM)  | 650  | RIM REC  | DW 23 B         |
| OD (MM)  | 1830 | ECE      | E11-106R-005103 |
| SLR (MM) | 830  | SRI      | 875             |
| RC (MM)  | 5510 | TRA CODE | R1W             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|---------------|------|------|------|------|------|------|------|------|
| 70            | 2475 | 2900 | 3320 | 3690 | 4060 | 4375 | 4900 | 5275 |
| FROM 65 TO 40 | 2725 | 3190 | 3650 | 4060 | 4465 | 4810 | 5390 | 5800 |
| 30            | 2830 | 3315 | 3795 | 4220 | 4640 | 5000 | 5605 | 6030 |
| 20            | 2940 | 3445 | 3940 | 4380 | 4820 | 5190 | 5820 | 6260 |
| 10            | 3460 | 4050 | 4635 | 5155 | 5670 | 6105 | 6845 | 7365 |
| UPTO 30 CYC   | 3540 | 4145 | 4745 | 5275 | 5800 | 6250 | 7005 | 7540 |
| UPTO 15 CYC   | 4220 | 4940 | 5655 | 6290 | 6920 | 7455 | 8350 | 8990 |
| UPTO 10 CYC   | 4630 | 5420 | 6025 | 6900 | 7590 | 8175 | 9160 | 9860 |
| 10HT          | 2830 | 3315 | 3795 | 4220 | 4640 | 5000 | 5605 | 6030 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.