

AGRIMAX RT 657

TIRE SIZE	540/65 R 38
UM	US STANDARD
MACHINERY	TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	153 D ; 156 A8



ABMESSUNGEN US STANDARD

USA-CODE	94029167	RIM REC	W 16 L
SW (IN)	20.9	RIM ALT	W 18 L
OD (IN)	65.6	ECE	E4-106R-000589
SLR (IN)	29.9	TRA CODE	R1W
RC (IN)	199.2	TREAD DEPTH (32nd)	62.37

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	3870	4510	5070	5630	6210	6680	7410	8050
30	4070	4740	5330	5920	6510	7020	7780	8450
25	4230	4940	5560	6170	6790	7320	8110	8820
20	4450	5190	5840	6480	7130	7690	8520	9260
5 LT	5180	6050	6800	7560	8310	8960	9930	10790
5 HT	4450	5190	5840	6480	7130	7690	8520	9260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.