


# AGRIMAX PROCROP

TIRE SIZE	VF 230/95 R 48
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZADOR AGRÍCOLA
VERSÃO	STEEL BELTED
TIRE TYPE	TL
LI/SS	148 D



## DIMENSÕES IS STANDARD

SW (MM)	233	RIM REC	W8
OD (MM)	1660	RIM ALT	W7
SLR (MM)	785	ECE	E11-106R-0011158
RC (MM)	5100	SRI	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1350	1525	1695	1840	2040	2155	2355	2555	2730	2870
FROM 65 TO 40	1485	1670	1860	2020	2240	2365	2585	2805	2995	3150
30	1515	1705	1900	2060	2285	2415	2640	2865	3055	3215
20	1545	1740	1940	2100	2330	2460	2690	2920	3120	3280
10	1630	1840	2045	2220	2465	2600	2845	3085	3295	3465
UPTO 15 CYC.	2010	2265	2520	2735	3035	3205	3505	3805	4060	4270
UPTO 30 CYC.	1685	1900	2115	2295	2545	2685	2940	3190	3405	3580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.