


AGRIMAX RT 657

TIRE SIZE	340/65 R 20
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAKTOR / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	124 D ; 127 A8



DIMENSIONER US STANDARD

USA CODE	94042005	RC (IN)	113.9
SW (IN)	13.5	RIM REC	W 11
OD (IN)	37.4	RIM ALT	W 10 ; W 12
SLR (IN)	16.9	ECE	E4-106R-001413

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	1660	1940	2230	2470	2720	2930	3250	3530
30	1740	2040	2340	2600	2850	3080	3420	3700
25	1820	2130	2440	2700	2980	3210	3550	3860
20	1910	2240	2560	2840	3130	3370	3740	4060
5 LT	2230	2600	2990	3320	3650	3940	4350	4730
5 HT	1910	2240	2560	2840	3130	3370	3740	4060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.