

FLOTATION 648

TIRE SIZE	600/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	153 A8/149 B
LI/SS FREE ROLLING	165 A8/161 B



DIMENSIONER US STANDARD

USA CODE	94006403	RC (IN)	137.8
SW (IN)	24.1	RIM REC	AG 20.00
OD (IN)	46.1	ECE	E4-106R-002306
SLR (IN)	20.1	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	32	35	38
5 FR	14420	15170	15890
10 FR	12970	13660	14310
20 FR	11530	12140	12720
25 FR	10300	10840	11350
30 FR	9270	9750	10200
5 DW	10220	10760	11260
10 DW	9190	9680	10140
20 DW	8170	8610	9020
25 DW	7300	7680	8050
30 DW	6570	6910	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.