


MULTIMAX MP 513

| | |
|---------------------|--|
| TIRE SIZE | 375/70 R 20 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VEICULO UNIVERSAL / CAMIÃO DE FERTILIZANTES / VEICULO UNIVERSAL |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 136 G |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|--|
| CÓDIGO USA | 94051847 | RC (IN) | 122.9 |
| SW (IN) | 14.8 | RIM REC | 12 |
| OD (IN) | 40.7 | RIM ALT | W 10; DW 10; 11; 11 SDC; W 11; DW 11; 12 SDC |
| SLR (IN) | 18.6 | ECE | E11-54R-0016139 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 |
|-----------|------|------|------|------|------|
| 55 | 2670 | 3160 | 3760 | 4350 | 4940 |
| 40 | 2900 | 3440 | 4090 | 4730 | 5370 |
| 25 | 3080 | 3650 | 4330 | 5020 | 5690 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.