


# AGRIMAX RT 600



<b>TYRE SIZE</b>	<b>IF 710/75 R 34 CFO</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / IMPLEMENTS
<b>VERSION</b>	STEEL BELTED
<b>TL/TT</b>	TL
<b>LI/SS</b>	184 A8/B

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94512317	<b>RC (IN)</b>	227.2
<b>SW (IN)</b>	28.1	<b>RIM REC</b>	DW25 B
<b>OD (IN)</b>	75.6	<b>RIM ALT</b>	DW23 B
<b>SLR (IN)</b>	33.7	<b>ECE</b>	E11-106R-0010577

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
<b>30</b>	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
<b>25</b>	7740	9130	10520	11710	13090	14290	15670	16860	18450	19840
<b>10</b>	8910	10500	12100	13470	15070	16430	18030	19400	21230	22820
<b>5</b>	9830	11600	13360	14870	16630	18140	19910	21430	23430	25200
<b>UPTO 20 CYC</b>	10060	11870	13680	15220	17030	18570	20380	21920	24000	25790
<b>UPTO 10 CYC</b>	12000	14150	16300	18150	20300	22140	24300	26150	28600	30750
<b>UPTO 5 CYC</b>	13160	15520	17880	19910	22270	24290	26650	28670	31370	33730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.