

EARTHMAX SR 431



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 431




EARTHMAX SR 431 (E-4) is an All Steel tire specially designed for rigid haul trucks operating in severe mining conditions (surface and underground mines). The non-directional tread pattern ensures excellent traction and stability. The tire features a strong All Steel casing and a special tread compound providing extraordinary cut and chip resistance as well as a long service life even in rocky, abrasive and harsh environments.



SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
Ø25"	16.00 R 25	TL	E4	**	-	11.25/2.0	-	0	452	1532	713	4649	CRC UMS
	18.00 R 25	TL	SH4	****	-	13.00/2.5	-	0	520	1660	760	5040	CR
	18.00 R 25	TL	E4	**	185 B	13.00/2.5	-	140	520	1660	760	5040	CR
	16.00 R 25	TL	E4	**	177 B	11.25/2.0	-	166	452	1532	713	4649	CR
	16.00 R 25	TL	E4	***	183 B	11.25/2.0	-	166	452	1532	713	4649	CR

CRC UMS: CUT RESISTANT COMPOUND (UMS), CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E4/SH4	 B	 185 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width O.O. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index