


# AGRIMAXFACTOR

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>710/70 R 38</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TRACTOR  |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 166 D ; 169 A8   |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 716  | <b>RIM REC</b>  | DW 23 B         |
| <b>OD (MM)</b>  | 1959 | <b>ECE</b>      | E11-106R-007636 |
| <b>SLR (MM)</b> | 866  | <b>SRI</b>      | 925             |
| <b>RC (MM)</b>  | 5800 | <b>TRA CODE</b> | R1W             |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 2915 | 3395 | 3870 | 4350 | 4825 | 5300 |
| 50         | 3065 | 3565 | 4065 | 4565 | 5065 | 5565 |
| 40         | 3195 | 3720 | 4240 | 4765 | 5285 | 5805 |
| 30         | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |
| 10 LT      | 3910 | 4550 | 5190 | 5830 | 6470 | 7105 |
| 10 HT      | 3355 | 3905 | 4450 | 5000 | 5550 | 6095 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.